World-Leading Ultrafast FBG (UFBG) DEVICES

- HIGH PERFORMANCE
- High Consistency
- HIGH CUSTOMISABILITY



Product Catalog


Oct 2023




Innofocus Photonics Technology Pty Ltd

WHAT IS FIBRE BRAGG GRATING

Fibre Bragg Grating (FBG) is a miniaturised optical reflector built in an optical fibre that reflects particular wavelength of light and transmits all others. FBGs can be used broadly in optical sensing systems and optical communication systems. In the meantime, the ultra-narrow bandwidth of FBGs making it extremely suitable for high-power ultra-narrow band fibre lasers.





FBG HAVE VERSATILE APPLICATIONS IN ALMOST EVERY INDUSTRY




INDUSTRY CHALLENGES

Although FBGs are already widely used in a range of industries, achieving high performance, high consistency and high customisability are still challenges for FBGs to be applied to the following industries:



Extreme Environment Sensing

 Requires FBGs to have high temperature stability and high mechanical strength



High Power Fibre Lasers


 Requires FBGs to have ultra-high reflectivity and high power stability



Optical Communication Systems

 Requires FBGs to have ultra-narrow bandwidth for WDM devices

Innofocus Solved These Challenges Successfully with Femtosecond Lasers



Fabricated by UV and phase mask method



Fabricated by femtosecond ultrafast laser pulses

Conventional FBGs	Innofocus's Ultrafast FBGs
Low Mechanical Strength	High Mechanical Strength
Example 2 Low Temperature Stability	High Temperature Stability
S Low Fabrication Flexibility	Fully Customisable Fabrication
Small Dynamic Range	Large Dynamic Range


WORLD-LEADING FBG MANUFACTURING COMPANY

In response to the industry challenges, Innofocus has invested heavily in technology, hardware and software, fully committed to supporting more advanced research and development together with our customers. We have been awarded "Best Intelligent Laser Manufacturing Specialist 2022" by APAC Insider, as a recognition of our cuttingedge nano-manufacturing capabilities. Innofocus is one of the few companies in the world who is capable of producing fully customisable Ultrafast FBG devices with high performance and high consistency using the world-leading ultrafast laser intelligent nano fabrication technology.


PRODUCT PORTFOLIO

Ultrafast FBG (UFBG)














Sensors and Demodulators

UFBG Sensors









UFBG Temperature Sensor UFBG Pressure Sensor UFBG Strain Sensor UFBG Soil Pressure Sensor


Demodulators



IF-GD-i6 Signal Demodulator

ULTRAFAST FBG

Femtosecond Laser Fabricated FBG









HIGH PERFORMANCE HIGH CONSISTENCY HIGH CUSTOMISIBLITY

Applicable to Extreme Environment Sensing Systems, Optical Communication Systems, High Power Fibre Lasers.









UFBG_S

Femtosecond Laser Fabricated FBG
Standard Reflectivity



ULTRA-HIGH TEMPERATURE UFBG_S HIGH TEMPERATURE UFBG_S

- HIGH TEMPERATURE STABILITY
- HIGH PRESSURE STABILITY
- HIGH REFLECTIVITY
- High consistency
- BETTER CENTRAL WAVELENGTH CONTROL

Ultra-high Temperature UFBG_S



UFBG_S_PI_80_0.25

Femtosecond laser fabricated single FBG Standard reflectivity Fibre length 2m

Key Advantages

• Ultra-high temperature stability with PI coating




Without fused FC/APC or FC/PC connector





With fused FC/APC or FC/PC connector



Key Parameters		
Reflectivity	> 80%	
3 dB Bandwidth	< 0.25 nm	
Centre Wavelength	1460 nm - 1640 nm	
Side Lobe Suppression Ratio	> 15 dB	
Fibre Coating	Polyimide	
Grating Length	9 mm	



Ultra-high Temperature UFBG_S All Product Specifications

Item No.	Central Wavelength	Reflectivity	3dB Bandwidth	SLSR	Grating Length	Fibre Length	Fibre Coating
UFBG_S_PI_30_0.25	1460 nm – 1640 nm	> 30%	< 0.25 nm	> 15 dB	8.0 mm	2 m	Polyimide
UFBG_S_PI_30_0.40	1460 nm – 1640 nm	> 30%	< 0.40 nm	> 15 dB	5.0 mm	2 m	Polyimide
UFBG_S_PI_30_0.70	1460 nm – 1640 nm	> 30%	< 0.70 nm	> 15 dB	3.0 mm	2 m	Polyimide
UFBG_S_PI_60_0.25	1460 nm – 1640 nm	> 60%	< 0.25 nm	> 15 dB	8.0 mm	2 m	Polyimide
UFBG_S_PI_60_0.40	1460 nm – 1640 nm	> 60%	< 0.40 nm	> 15 dB	6.0 mm	2 m	Polyimide
UFBG_S_PI_60_0.70	1460 nm – 1640 nm	> 60%	< 0.70 nm	> 15 dB	3.0 mm	2 m	Polyimide
UFBG_S_PI_80_0.25	1460 nm – 1640 nm	> 80%	< 0.25 nm	> 15 dB	9.0 mm	2 m	Polyimide
UFBG_S_PI_80_0.40	1460 nm – 1640 nm	> 80%	< 0.40 nm	> 15 dB	7.0 mm	2 m	Polyimide

Customisable Configuration Table

Choose your own suitable parameters according to the following configuration table:

Key Parameters		
Reflectivity	From 5% to 80%	
Reflectivity Consistency	Within 5% deviation of the designed reflectivity	
3 dB Bandwidth	From 0.20 nm to 0.70 nm	
Side Lobe Suppression Ratio	> 15 dB	
Central Wavelength	From 1460 nm to 1640 nm	
Central Wavelength Deviation	± 0.25 nm	
Fibre Coating	Polyimide	
Fibre Length	Upon request	
Connector Service	With fused FC/APC or FC/PC connector upon request	

• Detailed information can be provided upon request.





UFBG_S_AC_80_0.25

Femtosecond laser fabricated single FBG Standard reflectivity Fibre length 2m

Reflectivity Spectrum




Without fused FC/APC or FC/PC connector





With fused FC/APC or FC/PC connector



Key Parameters		
Reflectivity	> 80%	
3 dB Bandwidth	< 0.25 nm	
Central Wavelength	1460 nm - 1640 nm	
Side Lobe Suppression Ratio	> 15 dB	
Fibre Coating	Acrylate	
Grating Length	9 mm	

High Temperature UFBG_S All Products Specifications

Item No.	Central Wavelength	Reflectivity	3dB Bandwidth	SLSR	Grating Length	Fibre Length	Fibre Coating
UFBG_S_AC_30_0.25	1460 nm – 1640 nm	> 30%	< 0.25 nm	> 15 dB	8.0 mm	2 m	Acrylate
UFBG_S_AC_30_0.40	1460 nm – 1640 nm	> 30%	< 0.40 nm	> 15 dB	5.0 mm	2 m	Acrylate
UFBG_S_AC_30_0.70	1460 nm – 1640 nm	> 30%	< 0.70 nm	> 15 dB	3.0 mm	2 m	Acrylate
UFBG_S_AC_60_0.25	1460 nm – 1640 nm	> 60%	< 0.25 nm	> 15 dB	8.0 mm	2 m	Acrylate
UFBG_S_AC_60_0.40	1460 nm – 1640 nm	> 60%	< 0.40 nm	> 15 dB	6.0 mm	2 m	Acrylate
UFBG_S_AC_60_0.70	1460 nm – 1640 nm	> 60%	< 0.70 nm	> 15 dB	3.0 mm	2 m	Acrylate
UFBG_S_AC_80_0.25	1460 nm – 1640 nm	> 80%	< 0.25 nm	> 15 dB	9.0 mm	2 m	Acrylate
UFBG_S_AC_80_0.40	1460 nm – 1640 nm	> 80%	< 0.40 nm	> 15 dB	7.0 mm	2 m	Acrylate

Customisable Configuration Table

Choose your own suitable parameters according to the following configuration table:

Key Parameters	Selectable Values
Reflectivity	From 5% to 80%
Reflectivity Consistency	Within 5% deviation of the designed reflectivity
3 dB Bandwidth	From 0.20 nm to 0.70 nm
Side Lobe Suppression Ratio	> 15 dB
Central Wavelength	From 1460 nm to 1640 nm
Central Wavelength Deviation	± 0.25 nm
Fibre Coating	Acrylate
Fibre Length	Upon request
Connector Service	With fused FC/APC or FC/PC connector upon request

• Detailed information can be provided upon request.



UFBG_W

Femtosecond Laser Fabricated FBG Array Low Reflectivity





ULTRA-LOW REFLECTIVITY

Down to < 0.001%, allowing for up to 100,000 FBG structures within one fibre

KILOMETRE-LENGTH SENSING

Able to continuously fabricate FBGs up to 5 km, extending the sensing range

HIGH SPATIAL RESOLUTION

Small grating spacing enabling higher sensing accuracy

FULLY CUSTOMISABLE



Customer Innovation & Practice Centre

service@innofocus.com.au

UFBG_W Array Example




UFBG_W_PI_100_0.05

Femtosecond laser fabricated FBG Array Weak reflectivity

Key Advantages

- **Ultra-low reflectivity** allowing for more sensing points within one fibre
- High spatial resolution allowing for higher sensing accuracy



Key Parameters		
Reflectivity	< 0.05%	
Quantity	100	
Central Wavelength	1460 nm - 1640 nm	
Grating Spacing	10 mm	
Fibre Coating	Polyimide	



UFBG_W Customisable Configuration Table

Choose your own suitable parameters according to the following configuration table:

Key Parameters	Selectable Values
Reflectivity	From < 1% down to < 0.001% (Fully customisable)
Grating Spacing	Down to 500 μm
Grating Length	Down to 30 μm
Quantity	Up to 100,000
Continuous Processing Length	Up to 5 km
Central Wavelength	From 1460 nm to 1640 nm
Central Wavelength Deviation	± 0.25 nm
Fibre Coating	Acrylate / Polyimide
Connector Service	With fused FC/APC or FC/PC connector upon request

• All UFBG_W products are produced according to customer specifications upon request.



SPECIALISED UFBG

Femtosecond Laser Fabricated FBG Devices with Fully Customised Reflectivity,
Bandwidth & Central Wavelength





HIGH PERFORMANCE
HIGH CONSISTENCY
HIGH CUSTOMISABILITY

MORE INNOVATIONS AT



Customer Innovation & Practice Centre

service@innofocus.com.au

Specialised UFBG Example 1





Without fused FC/APC or FC/PC connector





With fused FC/APC or FC/PC connector

Specialised_UFBG_AC_99.99%

Femtosecond laser fabricated Specialised UFBGs
Ultra-high reflectivity reaching 99.99%
Featured product for high-power fibre lasers application

Key Advantages

- Efficient Laser Cavity: Achieving 99.99% reflectivity, perfect for fibre laser cavity reflectors.
- High Power Handling & Long Lifetime: They handle high power, ensuring stability and extended lifespan.
- **Industry Pioneer**: Our Specialised UFBG_AC_99.99% is the world's first commercial 99.99% reflectivity product designed for fibre lasers applications.

Reflectivity Spectrum Device model: Specialised UFBG_AC_99.99% -65 -70 Reflectivity: 99.99% -75 -80 Return Loss (dB) -85 -90 -95 -100 -105 -110 1535 1540 1550 1560 1565 1530 1570 Wavelength (nm)

Key Parameters		
Reflectivity	> 99.99%	
3 dB Bandwidth	< 0.20 nm	
Central Wavelength	1460 nm - 1640 nm	
Fibre Coating	Acrylate	



Specialised UFBG Example 2





Without fused FC/APC or FC/PC connector





With fused FC/APC or FC/PC connector

Specialised_UFBG_AC_0.05nm


Femtosecond laser fabricated FBG Ultra-narrow bandwidth 0.05 nm Featured product for optical communications & sensing

Key Advantages

- Wavelength Division Multiplexing (WDM): Enables channel spacing as small as 0.05 nm, allowing for densely packed channels and high data capacity.
- **High Sensitivity**: Maximises sensitivity in sensing applications, enabling the detection of minuscule changes with high precision.

Reflectivity Spectrum

Device model: Specialised UFBG AC 0.05 nm



Key Parameters		
Reflectivity	> 80%	
3 dB Bandwidth	0.05 nm	
Central Wavelength	1460 nm - 1640 nm	
Fibre Coating	Acrylate	



Specialised UFBG Customisable Configuration Table

Choose your own suitable parameters according to the following configuration table:

Key Parameters	Selectable Values
Reflectivity	Up to > 99.99%
3 dB Bandwidth	Down to 0.05 nm
Side Lobe Suppression Ratio	Up to 22 dB
Central Wavelength	From 1460 nm to 1640 nm
Fibre Coating	Acrylate / Polyimide
Connector Service	With fused FC/APC or FC/PC connector upon request

• Detailed information can be provided upon request.






SENSORS AND DEMODULATORS





IMMUNE TO HUMIDITY, RADIOACTIVITY, CHEMICAL CORROSION, HAVE BROAD APPLICATIONS IN ALMOST EVERY INDUSTRY

Applicable Temperature up to 800 °C, Applicable Pressure up to 60 MPa



UFBG Sensors and Demodulators



UFBG Temperature Sensor

UFBG Temperature Sensor is featured for surface and internal temperature sensing and monitoring for various structures.

UFBG Temperature Sensors have extensive applications in constructions including factories, bridges, dams, tunnels and etc. They can also be broadly applied to industries such as oil and gas, power plant for fire protection purposes.


Key Parameters		
Temperature Sensing Range	-50 °C ~ +350 °C	
Accuracy	± 0.5 °C	
Resolution	± 0.1 °C	
Central Wavelength	1525 nm ~1565 nm	
Dimension	Ф10*110 mm	

• High temperature sensing range can be customised upon request.

- Oil & Gas Temperature Monitoring
- Mine Temperature Sensing
- Power Plant Temperature Monitoring



UFBG Sensors and Demodulators



UFBG Pressure Sensor

UFBG Pressure Sensors is featured for pressure sensing and monitoring in various industrial automation environments.

UFBG Pressure Sensors can be used to monitor the water level, gas pipeline pressure, long-term monitoring of oil well and oil tank pressure. UFBG Pressure Sensors demonstrate their high performance for long-term pressure monitoring of oil well between 0.01 MPa ~ 60 MPa.

Key Parameters		
Pressure Sensing Range	0.01 Mpa ~ 60 Mpa	
Accuracy	0.5% F·S	
Resolution	0.1% F·S	
Central Wavelength	1525 nm ~1565 nm	
Reflectivity	≥ 90 %	
Working Temperature Range	-50 °C ~ +120 °C	
Dimension	Ф 14 ~ 40*60 mm	

• Detailed information can be provided upon request.

- Oil Industry for Oil Well and Oil Tank Pressure Monitoring
- Gas Pipeline Pressure Monitoring
- Mine Pressure Monitoring



UFBG Sensors and Demodulators



UFBG Strain Sensor


UFBG Strain Sensors with narrow 3dB Bandwidth and can be used to monitor structural deformations of aircrafts, electricity generators, oil and gas tank surfaces, wind turbines and etc.

Key Parameters	
Strain Sensing Range	±2500 μ ε
Strain Coefficient	0.714 μ ε / pm
3 dB Bandwidth	0.25 nm
Central Wavelength	1525 nm ~1565 nm
Reflectivity	90%
Side Lobe Suppression Ratio	> 20 dB
Working Temperature Range	-40 °C ~ +120 °C
Dimension	37*8*0.8 mm
Weight	2.6 g

• Detailed information can be provided upon request.

- Aircrafts
- Electricity Generators
- Wind Turbines





UFBG Soil Pressure Sensor

UFBG Soil Pressure Sensors are featured for monitoring soil pressure. They are consisted of two welded stainless stall plates, as the external pressure adding onto the sensor surface, the sensors will convert the pressure to an optical signal which will be transmitted to a signal demodulator to realise soil pressure monitoring.

UFBG Soil Pressure Sensors are suitable for long-term soil pressure management in soil, dams, embankments, slopes, roadbeds and etc.

Key Parameters	
Soil Pressure Sensing Range	50 kPa~ 34500 kPa
Accuracy	0.5% F·S
Central Wavelength	1525 nm ~1565 nm
Working Temperature Range	-50 °C ~ +120 °C

• Detailed information can be provided upon request.

- Soil
- Dams
- Slopes
- Roadbeds





Front



Rear

IF-GD-i6 Demodulator

IF-GD-i6 Demodulator obtains 8 channels and customisable scanning frequency (from 1 Hz up to 1000 Hz), demodulating signals from all UFBG sensors listed above. The demodulator builds in a calibration wavelength reference module, and it ensures a long-term accuracy of \pm 2 pm when used between -10 °C ~ 55 °C.

Key Parameters	
No. of Channels	8
Sampling Frequency	1 - 1000 Hz
Central Wavelength	1528 nm ~1568 nm
Resolution	0.1 pm
Accuracy	± 2 pm
Detecting Dynamic Range	≥ 40 dB

• Detailed information can be provided upon request.

Common Applications

IF-GD-i6 Demodulator can work with a various of sensors:

- Temperature Sensors
- Pressure Sensors
- Strain Sensors
- Soil Pressure Sensors
- Displacement Sensors







CONTACT US

Customer Innovation and Practice Centre:

service@innofocus.com.au

Products and Solutions Inquiry:

sales@innofocus.com.au